

HI-SCAN™ 145180-2is

HEIMANN X-RAY TECHNOLOGY



Feature Highlights

- Universal X-ray system for palletized items
- Dual view concept shortens inspection times
- Excellent image presentation through optimized beam geometry
- Rugged roller conveyor, capacity 1000 kg / m, i.e. up to 5000 kg when evenly distributed
- Meets TSA requirements for skid size 1,2m x 1,2m x 1,65m, (48" x 48" x 65")
- HI-MAT ^{Plus} technology for advanced material discrimination
- Typical penetration: 37 mm of steel

HI-SCAN 145180-2is a state-of-the-art X-ray inspection system for scanning objects up to a size of 145 cm x 180 cm [57" / 71"] [W x H].

Due to the compact footprint and the large tunnel dimensions the imaging system is perfectly suited for the inspection of air cargo, freight and palletized goods.

The HS 145180-2is is equipped with two 160 kV generators in a 90° opposition thus providing a horizontal and a vertical view of the object (dual view). This particular screening method facilitates a reliable inspection of even tightly packed objects in only one process. The dual view concept shortens inspection times and increases the effectiveness of the screening procedure.

Its new, innovative user concept makes it as easy to handle as the single-view system.

Even with a second beam direction, this new system remains compact and highly space-saving.

The heavy duty roller conveyor (small pitch design) allows the screening of heavy objects; conveyor load up to 5000 kg (evenly distributed).

HI-SCAN 145180-2is the security concept for handling air cargo, freight and palletized goods.

General Specifications

Tunnel dimensions	1470 (W) x 1820 (H) [mm] • 57.8" (W) x 71.7" (H)
Max. object size	1450 (W) x 1800 (H) [mm] • 57.1" (W) x 70.9" (H)
Conveyor height¹⁾	approx. 570 mm (22.4")
Conveyor speed (adjustable with frequency converter)	typical 0.24 [m/s]
max. conveyor load even distributed over the whole conveyor	5000 kg (11,025 lbs) • 1000 kg/m (672 lbs/ft)
Resolution (wire detectability)	standard (view A): 36 AWG (0.13 mm) • typical (view A): 38 AWG (0.10 mm) standard (view B): 36 AWG (0.13 mm) • typical (view B): 38 AWG (0.10 mm)
Penetration (steel)²⁾	standard (view A): 35 mm • typical (view A): 37 mm standard (view B): 35 mm • typical (view B): 37 mm
X-ray dose / inspection (typical)	3.0 μ Sv (0.3 mrem)
Film safety	guaranteed up to ISO 1600 (33 DIN)
Duty cycle	100 %, no warm-up procedure required

X-ray Generator

Anode voltage • cooling	160 kV cp operated • hermetically sealed oil bath
Beam direction	VA: diagonal from side • VB: diagonal from bottom to top

Image Generating System

X-ray converter	L-shaped detector line
Grey levels stored	4096
Image presentation	B/W, color
Digital video memory	1280 x 1024 / 24 bit
Image evaluation functions	VARI-MAT, O ² , OS, HIGH electronic zoom: stepless enlargement up to 64-times
Monitor	Flat Panel LCD Monitor

Additional Features

Functions	fading-in of date/time, luggage counter, user id-number, luggage marking system (acoustic), display of operating mode, REVIEW-feature (to recall previously visible image areas), zoom overview, free programmable keys, USB 2.0 interface, stepless zoom
Options	HI-TIP, HI-SPOT, SEN, XPlore, IMS (Image Store System - stores up to 100,000 images), Xport

Installation Data

X-ray leakage	meets all applicable laws and regulations with respect to X-ray emitting devices.
CE-labelling	in compliance with guidelines 2004/108/EC, 2006/42/EC, 2006/95/EC
Sound pressure level	< 70 dB(A)
Operating- / storage temperature	0° - 40°C / -20°C - +60°C
Humidity	10% - 90% (non-condensing)
Power supply⁴⁾	standard: 230 VAC +10% / -15% • 50 Hz / 60 Hz \pm 3 Hz
Power consumption	approx. 2.2 kVA (without options)
Protection class system/keyboard	IP 20/IP 43
Dimensions • Weight⁵⁾	5637 (L) x 2160 (W) x 2545 (H) [mm] • approx. 3000 kg 221.9" (L) x 85" (W) x 100.2" (H) • approx. 6600 lbs
Mechanical construction	steel construction with steel panels, mounted on roller castors standard color(s): RAL 7016 (dark gray)

¹⁾

²⁾ Cond.: steel step wedge, CU wires, conveyor speed 0.2 m/s

³⁾

⁴⁾ different values optional

⁵⁾ approx. without control desk, keyboard, monitor(s), control cabinet, etc.

⁶⁾



For product information, sales or service, please go to www.smithsdetection.com/locations

Smiths Heimann GmbH, Im Herzen 4, 65205 Wiesbaden, Germany

Modifications reserved. 95593709 10/04/2018 © Smiths Detection Group Ltd. - In some cases, the figures contain options
HI-SCAN is a trademark of Smiths Detection Group Ltd.

smiths detection